



# Product Description

## MASTERColour CDM-TP

Range of protected, high-efficiency, discharge lamps with a stable colour over lifetime and a crisp, sparkling light to be used in open luminaires

### Benefits

- High lamp efficacy results in low operating costs and low heat generation
- Stable colour impression over lifetime
- Long lamp life compared with incandescent and halogen lamps
- Relatively low heat output enhances comfort for shoppers and staff
- All types have UV-Block filtering for reduced fading risks

### Features

- Warm or cool white colour impression
- Colour rendering good to excellent
- Lamp design is well-suited to be used in luminaires for power-spots (high intensity) and high-bay general lighting
- Double UV-Block quartz sleeves and a hard-glass outer bulb

### Application

- Shops and shop windows, offices and public buildings
- Decorative outdoor: floodlighting and pedestrian areas

### Warnings and Safety

- Lamps may use electronic or electromagnetic control gear
- Control gear must include end-of-life protection (IEC61167, IEC 62035)
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

# MASTERColour CDM-TP

## Versions



## Dimensional drawing

D

Product	D (max)	O	L (min)	L (max)	L	C (max)
MASTERColour CDM-TP 150W/942 PGX12-2 1CT/12	32.00 mm	8 mm	89 mm	93 mm	91 mm	149 mm
MASTERColour CDM-TP 70W/830 PG12-2 1CT/12	32.00 mm	7 mm	89 mm	93 mm	91 mm	149 mm
MASTERColour CDM-TP 70W/842 PG12-2 1CT/12	32.00 mm	6 mm	89 mm	93 mm	91 mm	149 mm
MASTERColour CDM-TP 150W/830 PGX12-2 1CT/12	32.00 mm	9 mm	89 mm	93 mm	91 mm	149 mm

### Controls and Dimming

Dimmable	No
----------	----

### Operating and Electrical

Re-ignition Time (Min) (Max)	15 min
------------------------------	--------

### General Information

Life To 20% Failures (Nom)	13000 h
----------------------------	---------

Life To 50% Failures (Nom)	16000 h
----------------------------	---------

Life To 5% Failures (Nom)	9000 h
---------------------------	--------

Operating Position	UNIVERSAL
--------------------	-----------

### Mechanical and Housing

Bulb Finish	Clear
-------------	-------

Bulb Shape	T31
------------	-----

## Approval and Application

Order Code	Full Product Name	Energy Consumption kWh/1000 h	Energy	
			Efficiency Label (EEL)	Mercury (Hg) Content (Nom)
928085909230	MASTERColour CDM-TP 70W/842 PG12-2 1CT/12	81 kWh	A	7.1 mg
928086909230	MASTERColour CDM-TP 70W/830 PG12-2 1CT/12	81 kWh	A	5.2 mg
928086209230	MASTERColour CDM-TP 150W/942 PGX12-2 1CT/12	165 kWh	A	12.2 mg
928087009230	MASTERColour CDM-TP 150W/830 PGX12-2 1CT/12	165 kWh	A+	15 mg

## Operating and Electrical (1/2)

## MASTERCcolour CDM-TP

Order Code	Full Product Name	Lamp			
		Current (EM) (Nom)	Voltage (Max)	Voltage (Min)	Voltage (Nom)
928085909230	MASTERCcolour CDM-TP 70W/842 PG12-2 1CT/12	0.98 A	98 V	82 V	90 V
928086909230	MASTERCcolour CDM-TP 70W/830 PG12-2 1CT/12	0.98 A	98 V	82 V	90 V

Order Code	Full Product Name	Lamp			
		Current (EM) (Nom)	Voltage (Max)	Voltage (Min)	Voltage (Nom)
928086209230	MASTERCcolour CDM-TP 150W/942 PGX12-2 1CT/12	1.8 A	104 V	88 V	96 V
928087009230	MASTERCcolour CDM-TP 150W/830 PGX12-2 1CT/12	1.8 A	106 V	90 V	98 V

### Operating and Electrical (2/2)

Order Code	Full Product Name	Power (Rated) (Nom)
928085909230	MASTERCcolour CDM-TP 70W/842 PG12-2 1CT/12	73.2 W
928086909230	MASTERCcolour CDM-TP 70W/830 PG12-2 1CT/12	73.2 W
928086209230	MASTERCcolour CDM-TP 150W/942 PGX12-2 1CT/12	150.1 W

Order Code	Full Product Name	Power (Rated) (Nom)
928087009230	MASTERCcolour CDM-TP 150W/830 PGX12-2 1CT/12	150.1 W

### General Information

Order Code	Full Product Name	Cap-Base
928085909230	MASTERCcolour CDM-TP 70W/842 PG12-2 1CT/12	PG12-2
928086909230	MASTERCcolour CDM-TP 70W/830 PG12-2 1CT/12	PG12-2

Order Code	Full Product Name	Cap-Base
928086209230	MASTERCcolour CDM-TP 150W/942 PGX12-2 1CT/12	PGX12-2
928087009230	MASTERCcolour CDM-TP 150W/830 PGX12-2 1CT/12	PGX12-2

### Luminaire Design Requirements

Order Code	Full Product Name	Bulb Temperature (Max)
928085909230	MASTERCcolour CDM-TP 70W/842 PG12-2 1CT/12	400 °C
928086909230	MASTERCcolour CDM-TP 70W/830 PG12-2 1CT/12	400 °C

Order Code	Full Product Name	Bulb Temperature (Max)
928086209230	MASTERCcolour CDM-TP 150W/942 PGX12-2 1CT/12	480 °C
928087009230	MASTERCcolour CDM-TP 150W/830 PGX12-2 1CT/12	480 °C

### Light Technical (1/2)

Order Code	Full Product Name	Chromaticity			
		Coordinate X (Nom)	Coordinate Y (Nom)	Colour Code	Colour Designation
928085909230	MASTERCcolour CDM-TP 70W/842 PG12-2 1CT/12	374	378	842	Cool White (CW)
928086909230	MASTERCcolour CDM-TP 70W/830 PG12-2 1CT/12	428	401	830	Warm white (WW)

Order Code	Full Product Name	Chromaticity			
		Coordinate X (Nom)	Coordinate Y (Nom)	Colour Code	Colour Designation
928086209230	MASTERCcolour CDM-TP 150W/942 PGX12-2 1CT/12	376	374	942	Cool White (CW)
928087009230	MASTERCcolour CDM-TP 150W/830 PGX12-2 1CT/12	444	407	830	Warm white (WW)

### Light Technical (2/2)

## MASTERColour CDM-TP

Order Code	Full Product Name	Correlated Colour Temperature (Nom)	Colour Rendering Index (Nom)	Lumen Maintenance 10000 h (Nom)	Lumen Maintenance 2000 h (Nom)	Lumen Maintenance 5000 h (Nom)	Luminous Efficacy (rated) (Nom)	Luminous Flux (Rated) (Nom)
928085909230	MASTERColour CDM-TP 70W/842 PG12-2 1CT/12	4200 K	89	70 %	85 %	75 %	77 lm/W	5600 lm
928086909230	MASTERColour CDM-TP 70W/830 PG12-2 1CT/12	3000 K	80	65 %	80 %	70 %	82 lm/W	6000 lm
928086209230	MASTERColour CDM-TP 150W/942 PGX12-2 1CT/12	4200 K	95	70 %	85 %	75 %	83 lm/W	12500 lm
928087009230	MASTERColour CDM-TP 150W/830 PGX12-2 1CT/12	3000 K	86	65 %	72 %	70 %	88 lm/W	13200 lm

