



# Product Description

## MASTER TL5 Circular

16 mm tube diameter circular fluorescent lamps with a choice of various diameters

### Benefits

- Slim 16 mm tube allows creation of extremely flat luminaires
- Allows appealing circular designs
- High lamp efficacy
- Good colour rendering
- Temperature independent light output
- Higher average system efficiency

### Features

- Perfect circular shape
- Highly efficient 3-band fluorescent coating
- Specifically designed for operation with electronic gear
- Can be ignited from -15 to +50 °C
- Amalgam technology

### Application

- Brings the benefits of TL5 lighting to an even wider range of attractive applications
- Suitable for a wide range of professional and semi-professional applications
- Ideal for use in shops, offices and public areas with non-traditional lay-outs
- Amalgam lamps are limited suitable for dimming applications

### Warnings and Safety


- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

# MASTER TL5 Circular

## Versions



## Dimensional drawing



Product	D (max)	D (min)	E (min)	E (max)	I (min)	I (max)
MASTER TL5 Circular 40W/840 1CT/10	18 mm	14 mm	293 mm	305 mm	260 mm	272 mm
MASTER TL5 Circular 22W/840 1CT/10	18 mm	14 mm	220 mm	230 mm	187 mm	197 mm

# MASTER TL5 Circular

## Approval and Application

Mercury (Hg) Content (Max)	4 mg
Mercury (Hg) Content (Nom)	4 mg

## Controls and Dimming

Dimmable	Yes
----------	-----

## General Information

Cap-Base	2GX13
Life To 50% Failures Preheat (Nom)	12000 h
LSF Preheat 16000 h Rated	10 %
LSF Preheat 20000 h Rated	1 %
LSF Preheat 2000 h Rated	99 %
LSF Preheat 4000 h Rated	99 %
LSF Preheat 6000 h Rated	96 %
LSF Preheat 8000 h Rated	89 %

## Light Technical

Chromaticity Coordinate X (Nom)	0.38
Chromaticity Coordinate Y (Nom)	0.38
Colour Code	840
Colour Designation	Cool White (CW)
Correlated Colour Temperature (Nom)	4000 K
Colour Rendering Index (Nom)	81
LLMF 12000 h Rated	77 %
LLMF 16000 h Rated	74 %
LLMF 2000 h Rated	91 %
LLMF 20000 h Rated	72 %
LLMF 4000 h Rated	87 %
LLMF 6000 h Rated	84 %
LLMF 8000 h Rated	81 %

## Mechanical and Housing

Bulb Shape	C-T5
------------	------

## Approval and Application

Order Code	Full Product Name	Energy Consumption kWh/1000 h
927965084013	MASTER TL5 Circular 22W/840 1CT/10	24 kWh
927965584013	MASTER TL5 Circular 40W/840 1CT/10	41 kWh

## Operating and Electrical

Order Code	Full Product Name	Lamp Current (Nom)	Power (Nom)
927965084013	MASTER TL5 Circular 22W/840 1CT/10	0.300 A	23.5 W



## MASTER TL5 Circular

Order Code	Full Product Name	Lamp Current (Nom)	Power (Nom)
927965584013	MASTER TL5 Circular 40W/840 1CT/10	0.320 A	40.5 W

### Light Technical

Order Code	Full Product Name	Luminous Efficacy (rated) (Nom)	Luminous Flux (Nom)	Luminous Flux (Rated) (Nom)
927965084013	MASTER TL5 Circular 22W/840 1CT/10	82 lm/W	1800 lm	1800 lm

Order Code	Full Product Name	Luminous Efficacy (rated) (Nom)	Luminous Flux (Nom)	Luminous Flux (Rated) (Nom)
927965584013	MASTER TL5 Circular 40W/840 1CT/10	83 lm/W	3300 lm	3300 lm

