



MASTER PL-C 2 Pin

MASTER PL-C 13W/830/2P 1CT/5X10BOX

Energy-saving compact fluorescent lamps; Compact long-arc low-pressure mercury discharge lamp; Envelope consists of 4 parallel narrow fluorescent tubes

Warnings and Safety

- Use only with electromagnetic control gear
- Lamp light technical and electrical characteristics are influenced by operating conditions, i.e. lamp ambient temperature and operating position
- Dimming is not possible
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General information		Colour Rendering Index,horiz (Nom)	
Cap base	G24D-1 [G24d-1]		82
Life to 10% failures (nom.)	6500 h	LLMF 2000 h Rated	92 %
Life to 50% failures (nom.)	10000 h	LLMF 4000 h Rated	87 %
LSF 2000 h Rated	99 %	LLMF 6000 h Rated	83 %
LSF 4000 h Rated	98 %	LLMF 8000 h Rated	81 %
LSF 6000 h Rated	92 %		
LSF 8000 h Rated	78 %		
Light technical		Operating and electrical	
Colour Code	830 [CCT of 3,000 K]	Power (Rated) (Nom)	13.4 W
Lamp Luminous Flux 25°C EL (Nom)	925 lm	Lamp current (nom.)	0.170 A
Lamp Luminous Flux (Nom)	925 lm		
Colour Designation	Warm white (WW)	Temperature	
Colour Temperature, horizontal (Nom)	3000 K	Design temperature (nom.)	28 °C
Lamp Luminous Efficacy EM (Nom)	69 lm/W		
		Controls and dimming	
		Dimmable	No

MASTER PL-C 2 Pin

Mechanical and housing

Cap-base information 2P

Approval and application

Mercury (Hg) content (nom.) 1.4 mg

Energy consumption kWh/1,000 hours 17 kWh

Product data

Full product code 871150026922500

Order product name MASTER PL-C 13W/830/2P 1CT/5X10BOX

EAN/UPC – product 8711500269225

Order code 927904883001

SAP numerator – quantity per pack 1


Numerator – packs per outer box 50

SAP material 927904883001

Copy Net Weight (Piece) 53.600 g

ILCOS code FSQ-13/30/1B-I-G24d=1


Dimensional drawing




MASTER PL-C 13W/830/2P 1CT/5X10BOX

Product	D (max)	D1 (max)	A (max)	B (max)	C (max)
MASTER PL-C 13W/830/2P 1CT/5X10BOX	27.1 mm	27.1 mm	97.5 mm	117.0 mm	139.4 mm

Photometric data



Lightcolour /830



Lightcolour /830

MASTER PL-C 2 Pin

Lifetime



LDLE_PLC2P_0001-Life expectancy diagram

LDLE_PLC2P_0002-Life expectancy diagram



LDLM_PLC2P_0001-Lumen maintenance diagram

