



# MASTER PL-T TOP 4 Pin



## MASTER PL-T TOP 32W/840/4P 1CT/5X10BOX

Energy saving compact fluorescent lamp Compact long-arc low-pressure mercury discharge lamp Envelope consists of 6 parallel narrow fluorescent tubes Amalgam controlled operation

### Warnings and Safety

- Lamp light technical and electrical characteristics are influenced by operating conditions, i.e. lamp ambient temperature and operating position as well as applied HF control gear
- Shorter lamp life when often switching and not well pre-heated electrodes
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

### Product data

General Information	
Cap base	GX24Q-3 [ GX24q-3]
Life to 50% failures preheat (nom.)	13000 h
LSF preheat 2,000 hours rated	99 %
LSF preheat 4,000 hours rated	98 %
LSF preheat 6,000 hours rated	97 %
LSF preheat 8,000 hours rated	90 %
	Sphere
Light Technical	
Colour Code	840 [ CCT of 4,000 K]
Lamp Luminous Flux 25°C EL (Nom)	2300 lm
Lamp Luminous Flux (Nom)	2400 lm
Colour Designation	Cool White (CW)

Chromaticity coordinate X (nom.)	0.38
Chromaticity coordinate Y (nom.)	0.38
Colour Temperature, horizontal (Nom)	4000 K
Lamp Luminous Efficacy EM (Min)	75 lm/W
Colour Rendering Index, horiz (Nom)	80
LLMF 2000 h Rated	92 %
LLMF 4000 h Rated	88 %
LLMF 6000 h Rated	85 %
LLMF 8000 h Rated	84 %
LLMF 12000 h Rated	81 %


Operating and Electrical	
Power (Rated) (Nom)	34.5 W

# MASTER PL-T TOP 4 Pin

Lamp current (nom.)	0.320 A
<b>Temperature</b>	
Design temperature (nom.)	28 °C
<b>Controls and Dimming</b>	
Dimmable	Yes
<b>Mechanical and Housing</b>	
Cap-base information	4P
<b>Approval and Application</b>	
Energy Efficiency Class	G
Mercury (Hg) content (max.)	1.4 mg
Mercury (Hg) content (nom.)	1.4 mg

Energy consumption kWh/1,000 hours	35 kWh 423329
<b>Product Data</b>	
Full product code	871150056026170
Order product name	MASTER PL-T TOP 32W/840/4P 1CT/5X10BOX
EAN/UPC – product	8711500560261
Order code	927911984069
SAP numerator – quantity per pack	1
Numerator – packs per outer box	50
SAP material	927911984069
SAP net weight (piece)	70.000 g
ILCOS code	FSMH-32/40/1B-L/P-GX24q=3


## Dimensional drawing




MASTER PL-T TOP 32W/840/4P 1CT/5X10BOX

Product	D (max)	A (max)	B (max)	C (max)
MASTER PL-T TOP 32W/840/4P 1CT/5X10BOX	41 mm	98.7 mm	123.0 mm	138.7 mm

## Photometric data



Lightcolour /840



Lightcolour /840

# MASTER PL-T TOP 4 Pin

## Lifetime



LDLM\_PLTTOP4P\_0001-Lumen maintenance diagram

LDLE\_PLTTOP4P\_0001-Life expectancy diagram



LDLE\_PLTTOP4P\_0002-Life expectancy diagram

