



MASTER TL5 High Efficiency

MASTER TL5 HE 35W/830 SLV/40

Low-pressure mercury discharge lamps with a tubular 16 mm envelope

Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General Information		Operating and Electrical	
Cap base	G5 [G5]	Lamp Luminous Efficacy EM (Nom)	94 lm/W
Life to 50% failures preheat (nom.)	24000 h	Colour Rendering Index,horiz (Max)	85
Features	na [Not Applicable]	Colour Rendering Index,horiz (Min)	80
System description	High Efficiency	Colour Rendering Index,horiz (Nom)	82
LSF preheat 2,000 hours rated	99 %	LLMF 2000 h Rated	96 %
LSF preheat 4,000 hours rated	99 %	LLMF 4000 h Rated	95 %
LSF preheat 6,000 hours rated	99 %	LLMF 6000 h Rated	94 %
LSF preheat 8,000 hours rated	99 %	LLMF 8000 h Rated	93 %
LSF preheat 16,000 hours rated	97 %	LLMF 12000 h Rated	92 %
LSF preheat 20,000 hours rated	84 %	LLMF 16000 h Rated	91 %
		LLMF 20000 h Rated	90 %
Light Technical		Temperature	
Colour Code	830 [CCT of 3,000 K]	Design temperature (nom.)	35 °C
Lamp Luminous Flux 25°C EL (Nom)	3650 lm		
Lamp Luminous Flux (Nom)	3325 lm		
Colour Designation	Warm white (WW)		
Luminous Efficacy (@ Max Lumen, Rated) (Nom)	104 lm/W		
Colour Temperature, horizontal (Nom)	3000 K		

MASTER TL5 High Efficiency

Controls and Dimming

Dimmable	Yes
----------	-----

Mechanical and Housing

Cap-base information	Green Plate
----------------------	-------------

Approval and Application

Energy efficiency label (EEL)	A+
Mercury (Hg) content (nom.)	1.4 mg
Energy consumption kWh/1,000 hours	38 kWh

Product Data

Full product code	871150063950955
-------------------	-----------------

Order product name	MASTER TL5 HE 35W/830 SLV/40
EAN/UPC – product	8711500639509
Order code	927927083055
SAP numerator – quantity per pack	1
Numerator – packs per outer box	40
SAP material	927927083055
SAP net weight (piece)	127.400 g
ILCOS code	FDH-35/30/1B-L/P-G5-16/1450



Dimensional drawing



Product	D (max)	A (max)	B (max)	B (min)	C (max)
MASTER TL5 HE 35W/830 SLV/40	17 mm	1449.0 mm	1456.1 mm	1453.7 mm	1463.2 mm

TL5 HE 35W/830/GP

Photometric data




Lightcolour /830

Lightcolour /830

MASTER TL5 High Efficiency

Lifetime



LDLE_TL5-HE8_0001-Life expectancy diagram

LDLE_TL5-HE8_0002-Life expectancy diagram



LDLM_TL5-HE8_0001-Lumen maintenance diagram

