



# TL-E LIFEMAX Standard Colours

## TL-E 40W/54-765 1CT/20

This circular TL lamp (tube diameter 29 mm) enables omni-directional light distribution. It is suitable for use in a wide range of luminaires for various purposes where color rendering is not important.


### Product data

| General Information                   |               |
|---------------------------------------|---------------|
| Cap base                              | G10Q [ G10q]  |
| Life to 50% failures (nom.)           | 13000 h       |
| Light Technical                       |               |
| Colour Code                           | 54-765        |
| Lamp Luminous Flux 25°C EL (Nom)      | 2500 lm       |
| Colour Designation                    | Cool Daylight |
| Lumen maintenance 10,000 hours (nom.) | 73 %          |
| Lumen maintenance 2,000 hours (nom.)  | 87 %          |
| Lumen maintenance 5,000 hours (nom.)  | 78 %          |
| Colour Temperature, horizontal (Nom)  | 6200 K        |
| Lamp Luminous Efficacy EM (Nom)       | 62 lm/W       |
| Colour Rendering Index, horiz (Nom)   | 72            |
| Operating and Electrical              |               |
| Power (Rated) (Nom)                   | 40.0 W        |
| Lamp current (nom.)                   | 0.420 A       |
| Voltage (Nom)                         | 110 V         |
| Controls and Dimming                  |               |
| Dimmable                              | Yes           |

| Mechanical and Housing            |                            |
|-----------------------------------|----------------------------|
| Bulb shape                        | C-T9 [ C-T 29 mm (C-T9)]   |
| Approval and Application          |                            |
| Mercury (Hg) content (nom.)       | 9 mg                       |
| Product Data                      |                            |
| Full product code                 | 871150055991301            |
| Order product name                | TL-E 40W/54-765 1CT/20     |
| EAN/UPC – product                 | 8711500559913              |
| Order code                        | 928027405436               |
| SAP numerator – quantity per pack | 1                          |
| Numerator – packs per outer box   | 20                         |
| SAP material                      | 928027405436               |
| SAP net weight (piece)            | 0.250 kg                   |
| ILCOS code                        | FSC-40/62/2A-E-G10q-29/400 |

# TL-E LIFEMAX Standard Colours


## Dimensional drawing




| Product                    | D (max) | D (min) | E (min)  | E (max)  | I (min)  | I (max)  |
|----------------------------|---------|---------|----------|----------|----------|----------|
| TL-E 40W/<br>54-765 1CT/20 | 30.9 mm | 27.1 mm | 393.7 mm | 406.4 mm | 341.0 mm | 347.7 mm |

TL-E 40W/54-765

## Photometric data



Lightcolour /54-765



Lightcolour /54-765

