



TL-E 80

TL-E 40W/865 1CT/20

Fluorescent lamps with a circular tube having a diameter of 26 mm


Product data

General information	
Cap base	G10Q [G10q]
Life to 50% failures (nom.)	13000 h
LSF 2000 h Rated	98 %
LSF 4000 h Rated	77 %
LSF 6000 h Rated	60 %
LSF 8000 h Rated	45 %
Light technical	
Colour Code	865 [CCT of 6,500 K]
Lamp Luminous Flux 25°C EL (Nom)	3070 lm
Lamp Luminous Flux (Nom)	3070 lm
Colour Designation	Cool Daylight
Colour Temperature, horizontal (Nom)	6500 K
Lamp Luminous Efficacy EM (Nom)	78 lm/W
Colour Rendering Index,horiz (Nom)	80
LLMF 2000 h Rated	89 %
LLMF 4000 h Rated	84 %
LLMF 6000 h Rated	81 %
LLMF 8000 h Rated	80 %
Operating and electrical	
Power (Rated) (Nom)	40.0 W
Lamp current (nom.)	0.420 A
Voltage (Nom)	110 V

Temperature	
Design temperature (nom.)	25 °C
Controls and dimming	
Dimmable	Yes
Mechanical and housing	
Bulb shape	C-T9 [C-T 29 mm (C-T9)]
Approval and application	
Mercury (Hg) content (nom.)	8 mg
Energy consumption kWh/1,000 hours	44 kWh
Product data	
Full product code	871150028601700
Order product name	TL-E 40W/865 1CT/20
EAN/UPC – product	8711500286017
Order code	928027486574
SAP numerator – quantity per pack	1
Numerator – packs per outer box	20
SAP material	928027486574
Copy Net Weight (Piece)	0.240 kg
ILCOS code	FSC-40/65/1B-E-G10q-29/400

TL-E 80

Dimensional drawing



TL-E 40W/865 1CT/20

Product	D (max)	D (min)	E (min)	E (max)	I (min)	I (max)
TL-E 40W/865	30.9 mm	27.1 mm	393.7 mm	406.4 mm	341.0 mm	347.7 mm
1CT/20						

