



Greenspace Flex

RS378B P11 927 PSD-E NB M55

Greenspace Flex, 11 W, 927 warm white, DALI, Finger-protected

GreenSpace Flex is performance portfolio dedicated to Hospitality segment for GC/GM countries. With modular design concept, the light engines and different trims could have multiply of combination to satisfy diversified customer's requirement.

Product data

General Information		Temperature	
Light source engine type	LED	Ambient temperature range	-20 to +45 °C
CE mark	-		
Light Technical		Controls and Dimming	
Luminous Flux	836 lumen	Dimmable	Yes
Correlated Color Temperature (Nom)	2700 K	Control interface	DALI
Luminous Efficacy (rated) (Nom)	76 lm/W		
Color rendering index (CRI)	>90	Mechanical and Housing	
Light source color	927 warm white	Housing Material	Aluminum Alloy
Optical cover/lens type	-	Optical cover/lens material	-
		Housing Color	Dark gray
		Optical cover/lens finish	-
Operating and Electrical		Approval and Application	
Input Voltage	220 to 240 V	Ingress protection code	IP20 [Finger-protected]
Line Frequency	50 or 60 Hz	Mech. impact protection code	IK04 [0.5 J standard plus]
Power Consumption	11 W	Protection class IEC	Safety class II
Power Factor (Fraction)	0.83		
Number of products on MCB of 16 A type B	-	Initial Performance (IEC Compliant)	
		Luminous flux tolerance	+/-10%

Greenspace Flex

Power consumption tolerance	+/-10%
Product Data	
Full product code	911401535871
Order product name	RS378B P11 927 PSD-E NB M55
Order code	911401535871

Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	36
Material Nr. (12NC)	911401535871
Full product name	RS378B P11 927 PSD-E NB M55

Dimensional drawing

