



Greenspace Flex

RS378B P11 927 PSD-E WB M55

Greenspace Flex, 11 W, 927 warm white, DALI, Finger-protected

GreenSpace Flex is performance portfolio dedicated to Hospitality segment for GC/GM countries. With modular design concept, the light engines and different trims could have multiply of combination to satisfy diversified customer's requirement.

Product data

General Information	
Light source engine type	LED
CE mark	-

Light Technical	
Luminous Flux	957 lumen
Correlated Color Temperature (Nom)	2700 K
Luminous Efficacy (rated) (Nom)	87 lm/W
Color rendering index (CRI)	>90
Light source color	927 warm white
Optical cover/lens type	-

Operating and Electrical	
Input Voltage	220 to 240 V
Line Frequency	50 or 60 Hz
Power Consumption	11 W
Power Factor (Fraction)	0.83
Number of products on MCB of 16 A type B	-

Temperature	
Ambient temperature range	-20 to +45 °C

Controls and Dimming	
Dimmable	Yes
Control interface	DALI

Mechanical and Housing	
Housing Material	Aluminum Alloy
Optical cover/lens material	-
Housing Color	Dark gray
Optical cover/lens finish	-

Approval and Application	
Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK04 [0.5 J standard plus]
Protection class IEC	Safety class II

Initial Performance (IEC Compliant)	
Luminous flux tolerance	+/-10%

Greenspace Flex

Power consumption tolerance	+/-10%
-----------------------------	--------

Product Data

Full product code	911401536071
Order product name	RS378B P11 927 PSD-E WB M55
Order code	911401536071

Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	36
Material Nr. (12NC)	911401536071
Full product name	RS378B P11 927 PSD-E WB M55

Dimensional drawing

