



# Greenspace Flex

## RS378B P15 927 PSD-E MB M55

Greenspace Flex, 15 W, 927 warm white, DALI, Finger-protected

GreenSpace Flex is performance portfolio dedicated to Hospitality segment for GC/GM countries. With modular design concept, the light engines and different trims could have multiply of combination to satisfy diversified customer's requirement.

### Product data

General Information	
Light source engine type	LED
CE mark	-

  

Light Technical	
Luminous Flux	1,170 lumen
Correlated Color Temperature (Nom)	2700 K
Luminous Efficacy (rated) (Nom)	78 lm/W
Color rendering index (CRI)	>90
Light source color	927 warm white
Optical cover/lens type	-

  

Operating and Electrical	
Input Voltage	220 to 240 V
Line Frequency	50 or 60 Hz
Power Consumption	15 W
Power Factor (Fraction)	0.9
Number of products on MCB of 16 A type B	-

Temperature	
Ambient temperature range	-20 to +45 °C

  

Controls and Dimming	
Dimmable	Yes
Control interface	DALI

  

Mechanical and Housing	
Housing Material	Aluminum Alloy
Optical cover/lens material	-
Housing Color	Dark gray
Optical cover/lens finish	-

  

Approval and Application	
Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK04 [0.5 J standard plus]
Protection class IEC	Safety class II

  

Initial Performance (IEC Compliant)	
Luminous flux tolerance	+/-10%

## Greenspace Flex

Power consumption tolerance	+/-10%
-----------------------------	--------

### Product Data

Full product code	911401536871
Order product name	RS378B P15 927 PSD-E MB M55
Order code	911401536871

Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	36
Material Nr. (12NC)	911401536871
Full product name	RS378B P15 927 PSD-E MB M55

## Dimensional drawing

