



# GreenSpace Flex

## RS378B P11 927 DMX-E NB M55

--

GreenSpace Flex is performance portfolio dedicated to Hospitality segment for GC/GM countries. With modular design concept, the light engines and different trims could have multiply of combination to satisfy diversified customer's requirement.

### Product data

General Information		Temperature	
Light source engine type	LED	Ambient temperature range	-20 to +45 °C
Light Technical		Controls and Dimming	
Luminous Flux	836 lumen	Dimmable	Yes
Correlated Color Temperature (Nom)	2700 K	Control interface	Dynamic DMX
Luminous Efficacy (rated) (Nom)	76 lm/W	Mechanical and Housing	
Color rendering index (CRI)	>90	Housing Material	Aluminum Alloy
Light source color	927 warm white	Optical cover/lens material	-
Optical cover/lens type	-	Housing Color	Dark gray
Operating and Electrical		Optical cover/lens finish	-
Input Voltage	220 to 240 V	Approval and Application	
Line Frequency	50 or 60 Hz	Ingress protection code	IP20 [Finger-protected]
Input Frequency	50 or 60 Hz	Mech. impact protection code	IK04 [0.5 J standard plus]
Power Consumption	11 W	Protection class IEC	Safety class II
Power Factor (Fraction)	0.9	CE mark	-
Number of products on MCB of 16 A type B	-	Initial Performance (IEC Compliant)	
		Luminous flux tolerance	+/-10%

# Greenspace Flex

Power consumption tolerance	+/-10%
<b>Product Data</b>	
Full product code	911401543071
Order product name	RS378B P11 927 DMX-E NB M55
Order code	911401543071
Numerator - Quantity Per Pack	1

Numerator - Packs per outer box	36
Material number (12NC)	911401543071
Full product name	RS378B P11 927 DMX-E NB M55



## Dimensional drawing

