



Greenspace Flex

RS378B P15 930 DMX-E MB M55

15 W

GreenSpace Flex is performance portfolio dedicated to Hospitality segment for GC/GM countries. With modular design concept, the light engines and different trims could have multiply of combination to satisfy diversified customer's requirement.

Product data

General Information		Temperature	
CE mark	-	Ambient temperature range	-20 to +45 °C
Light source engine type	LED		
Light Technical		Controls and Dimming	
Luminous Flux	1,170 lumen	Dimmable	Yes
Correlated Color Temperature (Nom)	3000 K	Control interface	Dynamic DMX
Luminous Efficacy (rated) (Nom)	78 lm/W		
Color rendering index (CRI)	>90	Mechanical and Housing	
Light source color	930 warm white	Housing Material	Aluminum Alloy
Optical cover/lens type	-	Optical cover/lens material	-
		Housing Color	Dark gray
		Optical cover/lens finish	-
Operating and Electrical		Approval and Application	
Line Frequency	50 or 60 Hz	Ingress protection code	IP20 [Finger-protected]
Input Voltage	220 to 240 V	Mech. impact protection code	IK04 [0.5 J standard plus]
Power Consumption	15 W	Protection class IEC	Safety class II
Power Factor (Fraction)	0.9		
Number of products on MCB of 16 A type B	-	Initial Performance (IEC Compliant)	
		Luminous flux tolerance	+/-10%

Greenspace Flex

Power consumption tolerance	+/-10%
-----------------------------	--------

Product Data

Full product code	911401544371
Order product name	RS378B P15 930 DMX-E MB M55
Order code	911401544371

Numerator - Quantity Per Pack	1
-------------------------------	---

Numerator - Packs per outer box	36
---------------------------------	----

Material Nr. (12NC)	911401544371
---------------------	--------------

Full product name	RS378B P15 930 DMX-E MB M55
-------------------	-----------------------------

Dimensional drawing

