



GreenPerform Batten G3 BN398C

BN398C LED20/CW L600 PSU WB TC

PMMA bowl/cover

GreenPerform batten BN398C is a cost competitive linear solution with good performance and multiple lumen output for retail and industry applications. It offers surface mount and suspension installations to cater for different mounting options. Its multiple optic designs accommodate different applications as well.

Product data

General information	
Lamp colour code	865 cool daylight
Optical cover/lens type	PM [PMMA bowl/cover]
Control interface	-
Protection class IEC	Safety class I (I)
Flammability mark	F [For mounting on normally flammable surfaces]
CE mark	CE mark
Number of products on MCB (16 A type B)	33
Light source engine type	LED

Operating and electrical	
Input Voltage	220-240 V
Input frequency	50 or 60 Hz
Inrush current	14 A
Power factor (min.)	0.9

Controls and dimming	
Dimmable	No

Mechanical and housing	
Housing material	Metal-Plastic
Optical cover/lens material	Polymethyl methacrylate
Optical cover/lens finish	Clear
Overall length	573 mm
Overall width	58 mm
Overall height	94 mm
Colour	White RAL 9003
Dimensions (height x width x depth)	94 x 58 x 573 mm

Approval and application	
Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK03 [0.35 J reinforced]

GreenPerform Batten G3 BN398C

Initial performance (IEC compliant)

Initial luminous flux (system flux)	2000 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	129 lm/W
Lamp colour temperature	6500 K
Colour Rendering Index	>80
Initial chromaticity	SDCM<5
Initial input power	15.5 W
Power consumption tolerance	+/-10%

Application conditions


Ambient temperature range	-20 to +40 °C
---------------------------	---------------

Product data

Full product code	692382863288500
Order product name	BN398C LED20/CW L600 PSU WB TC
EAN/UPC – product	6923828632885
Order code	911401588951
SAP numerator – quantity per pack	1
Numerator – packs per outer box	1
SAP material	911401588951
Net Weight (Piece)	1.099 kg



Dimensional drawing



BN398C LED20/CW L600 PSU WB TC

