



Elegant and Brighter

UNIBollard

UNIBollard is dedicated to light up public environments like parks, buildings outside areas and compound areas to bring you more bright light in the evening with safety and convenience. Its graceful appearance will enhance any public space.

Benefits

- Long-lasting working period
- IP68 connector for easy connection and reliability
- Anti-UV cover without concerns of yellowing

Features

- 0.3 M (0.45 M) /0.6 M/1.2 M height options
- Up to 1100 lm
- CRI80
- Look and feel: cylinder and cubic housing for alternatives
- 50,000 hours L70B50 @ ta 35 °C

Application

- Public spaces
- Residential gardens, pathways

Warnings and Safety

- Use an additional surge-protection device in the electrical circuit for lighting wiring.

Versions



Approval and Application

Mech. impact protection code IK06

Controls and Dimming

Dimmable No

General Information

CE mark -
 Light source colour 830 warm white
 Driver included Yes
 Flammability mark NO
 Light source replaceable No

Initial Performance (IEC Compliant)

Init. Corr. Colour Temperature 3000 K
 Init. Colour Rendering Index >80

Light Technical

Standard tilt angle posttop -

General Information

Order Code	Full Product Name	Optical cover/lens type
911401755232	BCP210 LED1000/WW 13W 100-240V Rec AL	PCO
911401755242	BCP211 LED1000/WW 13W 100-240V Rec AL	PCO
911401755252	BCP212 LED1000/WW 13W 100-240V Rec AL	PCO
911401755262	BCP310 LED760/WW 15W 100-240V Cyl BK	PCF
911401755272	BCP311 LED760/WW 15W 100-240V Cyl BK	PCF
911401755282	BCP312 LED760/WW 15W 100-240V Cyl BK	PCF

Initial Performance (IEC Compliant)

Order Code	Full Product Name	Initial luminous flux
911401755232	BCP210 LED1000/WW 13W 100-240V Rec AL	1000 lm
911401755242	BCP211 LED1000/WW 13W 100-240V Rec AL	1000 lm
911401755252	BCP212 LED1000/WW 13W 100-240V Rec AL	1000 lm

Order Code	Full Product Name	Initial luminous flux
911401755262	BCP310 LED760/WW 15W 100-240V Cyl BK	760 lm
911401755272	BCP311 LED760/WW 15W 100-240V Cyl BK	760 lm
911401755282	BCP312 LED760/WW 15W 100-240V Cyl BK	760 lm

Light Technical

Order Code	Full Product Name	Standard tilt angle side entry
911401755232	BCP210 LED1000/WW 13W 100-240V Rec AL	-
911401755242	BCP211 LED1000/WW 13W 100-240V Rec AL	-
911401755252	BCP212 LED1000/WW 13W 100-240V Rec AL	-

Order Code	Full Product Name	Standard tilt angle side entry
911401755262	BCP310 LED760/WW 15W 100-240V Cyl BK	-
911401755272	BCP311 LED760/WW 15W 100-240V Cyl BK	-
911401755282	BCP312 LED760/WW 15W 100-240V Cyl BK	-

Mechanical and Housing

Order Code	Full Product Name	Colour
911401755232	BCP210 LED1000/WW 13W 100-240V Rec AL	Aluminium and White
911401755242	BCP211 LED1000/WW 13W 100-240V Rec AL	Aluminium and White
911401755252	BCP212 LED1000/WW 13W 100-240V Rec AL	Aluminium and White

Order Code	Full Product Name	Colour
911401755262	BCP310 LED760/WW 15W 100-240V Cyl BK	Black and Aluminium
911401755272	BCP311 LED760/WW 15W 100-240V Cyl BK	Black and Aluminium
911401755282	BCP312 LED760/WW 15W 100-240V Cyl BK	Black and Aluminium

